



2011

Italiano
English


IKDW



IKDW

INOXKIT

IKGDP30C..



CURVA 30° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304



30° FIXED BEND INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	119	122	130	135	142	147	160	172	184	197	210	222	235	282	295	307
E	46	48	51	51	53	54	57	60	53	67	70	74	77	93	96	99
C	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54


IKGDP45C..



CURVA COIB. INOX 45° SALDATO A TIG DN80/130 AISI 316L SP 0,4 mm

EN 1856-1 T200 P1 W V2 L50040 O30


IKGDP90C..



CURVA COIB. INOX 90° SALDATO A TIG DN80/130 AISI 316L SP 0,4 mm

EN 1856-1 T200 P1 W V2 L50040 O30

IKTADPC..




TERMINALE ANTINTEMPERIE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304

ANTI DOWN-DRAUGHT TERMINAL INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
A	222	260	303	310	370	418	468	530	700	800	900	1000	-	-	-	-
H	325	375	405	405	405	405	405	405	405	405	405	405	-	-	-	-
B	165	200	200	250	250	250	310	310	330	250	300	330	-	-	-	-

IKDPERC..




ELEMENTO RACCOLTA CENERI CON ISPEZIONE QUADRA COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304

ASH COLLECTION RECTANGULAR SECTION INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	440	440	440	440	440	440	440	440	440	440	440	440	440	440	440	440
A	113	113	113	113	113	113	185	185	185	185	185	185	185	185	185	185
B	190	190	190	190	190	190	280	280	280	280	280	280	280	280	280	280
C	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54

IKRTC..



RACCORDO "T" 45° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304


45° TEE INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	-	-	-	-
H	423	458	498	526	564	582	664	738	880	952	1022	1092	-	-	-	-
A	228	248	270	288	312	330	372	412	500	544	586	628	-	-	-	-
B	54	54	54	54	54	54	54	54	54	54	54	54	-	-	-	-

IKCCDPC..




TERMINALE CINESE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304

RAIN CAP INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
A	250	300	400	400	500	500	500	600	720	720	850	850	850	1150	1250	1350
B	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65
H	190	190	230	230	250	250	270	270	300	300	330	330	330	360	370	380

IKTDPCU..



RACCORDO "T" 90° USCITA MONOPARETE Ø 80 COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304


90° TEE INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
A	123	123	123	123	123	123	123	123	-	-	-	-	-	-	-	-
B	90	100	115	125	140	150	175	200	-	-	-	-	-	-	-	-
C	54	54	54	54	54	54	54	54	-	-	-	-	-	-	-	-
H	190	190	190	190	190	190	190	190	-	-	-	-	-	-	-	-

IKPIASTRC..



PIASTRA DI PARTENZA CON SCARICO LATERALE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO AISI 304

BASE PLATE WITH DRAIN PLUG INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	154	154	154	154	154	154	154	154	154	154	154	154	154	154	154	154
H2	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
A	230	250	280	300	330	350	400	450	500	550	600	650	700	750	800	850




ACCESSORI

ACCESSORIES

INOXIT

IKCOLSS..



COLLARE A MURO INOX

WALL BRACKET IN STAINLESS STEEL

Dn	80	100	110	120	125	130	140	150	160	180	200	220	250	300	350	400
A	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	100
B	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50

IKCR..




COLLARE PER RITUBAZIONE INOX

BRACKET FOR RELINING IN STAINLESS STEEL

Dn	80	100	110	120	125	130	140	150	160	180	200	220	250	300
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

IKFPS5S..



FALDALE REGOLABILE 5/30 INOX DN 80 CON BASE ALLUMINIO SENZA/FASC ANTINTEMP

flashing adjustable 5°-30° inox DN 80 with base in aluminium without storm collar

Dn	80	100	110	120	125	130	140	150	160	180	200	220	250	300	350	400
H	120	120	130	130	150	150	150	150	160	170	180	210	210	230	200	200
A	370	400	400	450	450	450	450	450	450	500	600	600	600	650	700	700



INOX KIT s.r.l. BAGNACAVALLO

Via Libeccio 9/11 - 48012 Bagnacavallo (RA)

Tel. 0545 62475

Fax 0545 926575

info@inoxkit.it

INOX KIT s.r.l. MISANO

Via Cella Raibano 31 - 47843 Misano Adriatico (RN)

Tel. 0541 694237

Fax 0541 425874

misano@inoxkit.it

INOX KIT s.r.l. SAN LAZZARO di SAVENA

Via Caselle 71/A - 40068 San Lazzaro di Savena (BO)

Tel. 051 462373

Fax 051 6274534

bologna@inoxkit.it

