



2011

**Italiano**  
**English**

IKDWC




**IKDWC**

**INOXIT**





## IKDWCGDP30C..



CURVA 30° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE


30° FIXED BEND INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	119	122	130	135	142	147	160	172	184	197	210	222	235	282	295	307
E	46	48	51	51	53	54	57	60	53	67	70	74	77	93	96	99
C	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54

## IKDWCGDP45C..



CURVA 45° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE


45° FIXED BEND INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	119	126	137	143	160	164	184	197	215	234	252	270	287	334	352	369
E	72	390	390	390	390	390	390	390	390	390	390	390	145	164	172	179
C	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54

## IKDWCGDP90C..



CURVA 90° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

90° FIXED BEND INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1 T200 P1 W V2 L50040 O30


EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	160	180	190	200	215	225	250	275	231	367	392	417	-	-	-	-
B	100	120	130	140	155	165	190	215	261	307	332	357	-	-	-	-
A	54	54	54	54	54	54	54	54	54	54	54	54	-	-	-	-





## IKDWCTTCDPC..




TERMINALE TRONCO CONICO COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

VENTURI CONE TERMINAL INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	200	200	200	200	200	200	200	200	290	290	290	290	290	290	290	290

## IKDWCPIASTRC..



PIASTRA DI PARTENZA CON SCARICO LATERALE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE


BASE PLATE WITH DRAIN PLUG FOR DOUBLE INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	154	154	154	154	154	154	154	154	154	154	154	154	154	154	154	154
H2	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
A	230	250	280	300	330	350	400	450	500	550	600	650	700	750	800	850

## IKDWCPIASIC..




PIASTRA INTERMEDIA (SENZA SUPPORTI) COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

INTERMEDIATE ANCHOR PLATE INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

## IKDWCTADP..




TERMINALE ARCHITETTONICO COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

COPPER ARCHITECTURAL TERMINAL INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350								
H	200	200	200	400	400	400	400	400	-	-	-	-	-	-	-	-

## IKDWCCDPC..




TERMINALE CINESE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

RAIN CAP INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
A	250	300	400	400	500	500	500	600	720	720	850	850	850	1150	1250	1350
B	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65
H	190	190	230	230	250	250	270	270	300	300	330	330	330	360	370	380

## IKDWCTADPC..



TERMINALE ANTINTEMPERIE COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE


ANTI DOWN-DRAUGHT TERMINAL INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER

EN 1856-1

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
A	222	260	303	310	370	418	468	530	700	800	900	1000	-	-	-	-
H	325	375	405	405	405	405	405	405	405	405	405	405	-	-	-	-
B	165	200	200	250	250	250	310	310	330	250	300	330	-	-	-	-





## IKDWCFASCAC..



FASCETTA ANTINTEMPERIE - RAME NATURALE

STORM COLLAR - NATURAL COPPER

## IKDWCCOLTC..




COLLARE PER CAVI TIRANTI - RAME NATURALE

GUY WIRE BRACKET - NATURAL COPPER

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	450	500	550	600				
H	40	40	40	40	40	40	40	40	40	40	40	40	-	-	-	-

## IKDWCRTIC..



RACCORDO A "T" 45° COIBENTATO 25 mm - INTERNO INOX AISI 316L ED ESTERNO RAME NATURALE

45° TEE INSULATED 25 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL NATURAL COPPER


EN 1856-1 T200 P1 W V2 L50040 O30

EN 1856-1 T600 N1 W V2 L50040 O50 G70

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550				
H	423	458	498	526	564	582	664	738	880	952	1022	1092	-	-	-	-
A	228	248	270	288	312	330	372	412	500	544	586	628	-	-	-	-
B	54	54	54	54	54	54	54	54	54	54	54	54	-	-	-	-



FASCETTA DI SICUREZZA COPRIGIUNTO - RAME NATURALE



LOCKING BAND - NATURAL COPPER

Di	80	100	130	150	180	200	250	300	350	400	450	500	550	600	650	700
De	130	150	180	200	230	250	300	350	400	450	500	550	600	650	700	750
H	30	30	30	30	30	30	30	30	30	42	42	42	42	42	42	42



ACCESSORI

ACCESSORIES

**INOX**IT







**INOX KIT s.r.l. BAGNACAVALLO**

Via Libeccio 9/11 - 48012 Bagnacavallo (RA)

Tel. 0545 62475

Fax 0545 926575

[info@inoxkit.it](mailto:info@inoxkit.it)

**INOX KIT s.r.l. MISANO**

Via Cella Raibano 31 - 47843 Misano Adriatico (RN)

Tel. 0541 694237

Fax 0541 425874

[misano@inoxkit.it](mailto:misano@inoxkit.it)

**INOX KIT s.r.l. SAN LAZZARO di SAVENA**

Via Caselle 71/A - 40068 San Lazzaro di Savena (BO)

Tel. 051 462373

Fax 051 6274534

[bologna@inoxkit.it](mailto:bologna@inoxkit.it)

